

**isobutene, liquefied, under pressure****SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

|                                  |  |
|----------------------------------|--|
| <b>Product name</b>              | : isobutene, liquefied, under pressure   |
| <b>Synonyms</b>                  | : 1,1-dimethylethene; 1,1-dimethylethylene; 1,1-dimethylethylene, liquefied, under pressure; 1-propene, 2-methyl-; 2-methyl-1-propene; 2-methyl-1-propene, liquefied, under pressure; 2-methylpropene; 2-methylpropene, liquefied, under pressure; 2-methylpropylene; asym-dimethylethylene; asymmetrical-dimethylethylene, liquefied, under pressure; gamma-butylene; gamma-butylene, liquefied, under pressure; iso-butene; isobutene; isobutylene; isobutylene, liquefied petroleum gas; isopropylidenemethylene; methylpropene, liquified, under pressure; petroleumgas, liquefied, under pressure; propene, 2-methyl- |
| <b>Registration number REACH</b> | : 01-2119456616-32   |
| <b>Product type REACH</b>        | : Substance/mono-constituent   |
| <b>CAS number</b>                | : 115-11-7   |
| <b>EC index number</b>           | : 601-012-00-4   |
| <b>EC number</b>                 | : 204-066-3  |
| <b>RTECS number</b>              | : UD0890000  |
| <b>Molecular mass</b>            | : 56.11 g/mol  |
| <b>Formula</b>                   | : C4H8   |

**1.2. Relevant identified uses of the substance or mixture and uses advised against****1.2.1 Relevant identified uses**

Industrial and professional use. Before use: carry out a risk assessment

**1.2.2 Uses advised against**

No uses advised against known

**1.3. Details of the supplier of the safety data sheet****Supplier of the safety data sheet**

BALCHEM NV  
Westvaardijk 85  
B-1850 Grimbergen Belgium  
☎ +32 2 251 60 87  
✉ +32 2 252 17 51  
info.grimbergen@balchem.com

**Distributor of the product**

BALCHEM NV  
Westvaardijk 85  
B-1850 Grimbergen Belgium  
☎ +32 2 251 60 87  
✉ +32 2 252 17 51  
info.grimbergen@balchem.com

**1.4. Emergency telephone number**

24h/24h (Telephone advice: English, French, German, Dutch):  
+32 14 58 45 45 (BIG)

**SECTION 2: Hazards identification****2.1. Classification of the substance or mixture**

Classified as dangerous according to the criteria of Regulation (EC) No 1272/2008

| Class      | Category      | Hazard statements   |
|------------|---------------|---|
| Flam. Gas  | category 1    | H220: Extremely flammable gas.                            |
| Press. Gas | Liquefied gas | H280: Contains gas under pressure; may explode if heated. |

**2.2. Label elements**

# isobutene, liquefied, under pressure

**Signal word**

Danger

**H-statements**

H220

Extremely flammable gas.

H280

Contains gas under pressure; may explode if heated.

**P-statements**

P210

Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

P381

Eliminate all ignition sources if safe to do so.

P377

Leaking gas fire: Do not extinguish, unless leak can be stopped safely.

P410 + P403

Protect from sunlight. Store in a well-ventilated place.

## 2.3. Other hazards

May build up electrostatic charges: risk of ignition

May be ignited by sparks

Gas/vapour spreads at floor level: ignition hazard

May cause frostbites

Slightly irritant to respiratory organs

Large spills/in enclosed spaces: risk of oxygen deficiency

Slightly irritant to eyes

Harmful to fishes

Harmful to invertebrates (Daphnia)

Harmful to algae

## SECTION 3: Composition/information on ingredients

### 3.1. Substances

| Name<br>REACH Registration No       | CAS No<br>EC No       | Conc. (C) | Classification according to CLP                          | Note    | Remark           |
|-------------------------------------|-----------------------|-----------|--|---------|------------------|
| 2-methylpropene<br>01-2119456616-32 | 115-11-7<br>204-066-3 | C>99 %    | Flam. Gas 1; H220<br>Press. Gas - Liquefied gas;<br>H280 | (1)(10) | Mono-constituent |

(1) For H-statements in full: see heading 16

(10) Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006

### 3.2. Mixtures

Not applicable

## SECTION 4: First aid measures

### 4.1. Description of first aid measures

**General:**

Check the vital functions. Unconscious: maintain adequate airway and respiration. Respiratory arrest: artificial respiration or oxygen. Cardiac arrest: perform resuscitation. Victim conscious with laboured breathing: half-seated. Victim in shock: on his back with legs slightly raised. Vomiting: prevent asphyxia/aspiration pneumonia. Prevent cooling by covering the victim (no warming up). Keep watching the victim. Give psychological aid. Keep the victim calm, avoid physical strain. Depending on the victim's condition: doctor/hospital.

**After inhalation:**

Remove the victim into fresh air. Respiratory problems: consult a doctor/medical service.

**After skin contact:**

In case of frostbites: Wash immediately with lots of water (15 minutes)/shower. Do not apply (chemical) neutralizing agents. Remove clothing while washing. Do not remove clothing if it sticks to the skin. Cover wounds with sterile bandage. Consult a doctor/medical service. If burned surface > 10%: take victim to hospital.

**After eye contact:**

Rinse immediately with plenty of water for 15 minutes. Do not apply neutralizing agents. Take victim to an ophthalmologist if irritation persists.

**After ingestion:**

Not applicable.

### 4.2. Most important symptoms and effects, both acute and delayed

#### 4.2.1 Acute symptoms

**After inhalation:**

EXPOSURE TO HIGH CONCENTRATIONS: Dizziness. Headache. Irritation of the respiratory tract. Ringing in the ears. Narcosis. Mental confusion. Excited/restless. Coordination disorders. Disturbances of consciousness. Increased salivation. Respiratory difficulties.

**After skin contact:**

Frostbites.

Publication date: 2015-07-02

Reference number: 1260

Product number: 10340

Revision number: 0000

2 / 10

# isobutene, liquefied, under pressure

**After eye contact:**

Redness of the eye tissue. EXPOSURE TO HIGH CONCENTRATIONS: Irritation of the eye tissue.

**After ingestion:**

Not applicable.

**4.2.2 Delayed symptoms**

No effects known.

**4.3. Indication of any immediate medical attention and special treatment needed**

If applicable and available it will be listed below.

## SECTION 5: Firefighting measures

**5.1. Extinguishing media****5.1.1 Suitable extinguishing media:**

Water spray. Polyvalent foam. BC powder. Carbon dioxide.

**5.1.2 Unsuitable extinguishing media:**

Solid water jet ineffective as extinguishing medium.

**5.2. Special hazards arising from the substance or mixture**

Upon combustion: CO and CO<sub>2</sub> are formed.

**5.3. Advice for firefighters****5.3.1 Instructions:**

If no hazard for/from the surroundings: controlled burning. If hazardous substances are nearby: consider extinguishment. Extinguish only if gas supply/leak can be shut afterwards. Cool tanks/drums with water spray/remove them into safety. Physical explosion risk: extinguish/cool from behind cover. Do not move the load if exposed to heat. After cooling: persistent risk of physical explosion.

**5.3.2 Special protective equipment for fire-fighters:**

Insulating gloves. Protective clothing. Large spills/in enclosed spaces: compressed air apparatus. Heat/fire exposure: compressed air/oxygen apparatus.

## SECTION 6: Accidental release measures

**6.1. Personal precautions, protective equipment and emergency procedures**

Keep upwind. Seal off low-lying areas. Close doors and windows of adjacent premises. Stop engines and no smoking. No naked flames or sparks. Spark- and explosionproof appliances and lighting equipment. Avoid ingress of water in the containers.

**6.1.1 Protective equipment for non-emergency personnel**

See heading 8.2

**6.1.2 Protective equipment for emergency responders**

Insulating gloves. Protective clothing. Large spills/in enclosed spaces: compressed air apparatus.

Suitable protective clothing

See heading 8.2

**6.2. Environmental precautions**

Contain released substance, pump into suitable containers. Plug the leak, cut off the supply. Dam up the liquid spill. Tip the container on one side to stop the leakage. Try to reduce evaporation. Prevent spreading in sewers.

**6.3. Methods and material for containment and cleaning up**

Prevent evaporation by covering with: sand, earth, vermiculite or powdered limestone. Shovel into closing drums. Carefully collect the spill/leftovers. Damaged/cooled tanks must be emptied. Do not use compressed air for pumping over spills. Take collected spill to manufacturer/competent authority. Wash clothing and equipment after handling.

**6.4. Reference to other sections**

See heading 13.

## SECTION 7: Handling and storage

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

**7.1. Precautions for safe handling**

Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Gas/vapour heavier than air at 20°C. Observe normal hygiene standards. Keep container tightly closed.

**7.2. Conditions for safe storage, including any incompatibilities****7.2.1 Safe storage requirements:**

Storage temperature: <50 °C. Keep out of direct sunlight. Ventilation at floor level. Fireproof storeroom. Provide for an automatic sprinkler system. Provide for a tub to collect spills. Provide the tank with earthing. Store only in a stabilized state. Under a shelter/in the open. Detached building. Meet the legal requirements.

**7.2.2 Keep away from:**

Heat sources, ignition sources, combustible materials, oxidizing agents, (strong) acids, halogens.

**7.2.3 Suitable packaging material:**

Steel, stainless steel, monel steel, aluminium, synthetic material, polyethylene, copper.

**7.2.4 Non suitable packaging material:**

Publication date: 2015-07-02

Reference number: 1260

Product number: 10340

Revision number: 0000

3 / 10

# isobutene, liquefied, under pressure

No data available

## 7.3. Specific end use(s)

If applicable and available, exposure scenarios are attached in annex. See information supplied by the manufacturer.

## SECTION 8: Exposure controls/personal protection

### 8.1. Control parameters

#### 8.1.1 Occupational exposure

##### a) Occupational exposure limit values

If limit values are applicable and available these will be listed below.

##### Belgium

|                        |  |                       |
|------------------------|--|-----------------------|
| Butène (tous isomères) | Time-weighted average exposure limit 8 h | 250 ppm               |
|                        | Time-weighted average exposure limit 8 h | 583 mg/m <sup>3</sup> |

##### USA (TLV-ACGIH)

|            |  |         |
|------------|--|---------|
| iso-Butene | Time-weighted average exposure limit 8 h (TLV - Adopted Value) | 250 ppm |
|------------|--|---------|

##### b) National biological limit values

If limit values are applicable and available these will be listed below.

#### 8.1.2 Sampling methods

If applicable and available it will be listed below.

#### 8.1.3 Applicable limit values when using the substance or mixture as intended

If limit values are applicable and available these will be listed below.

#### 8.1.4 DNEL/PNEC values

##### DNEL/DMEL - Workers

###### isobutene, liquefied, under pressure

| Effect level (DNEL/DMEL) | Type                                  | Value                  | Remark |
|--------------------------|---------------------------------------|------------------------|--------|
| DNEL                     | Long-term systemic effects inhalation | 769 mg/m <sup>3</sup>  |        |
|                          | Long-term local effects inhalation    | 1530 mg/m <sup>3</sup> |        |

##### DNEL/DMEL - General population

###### isobutene, liquefied, under pressure

| Effect level (DNEL/DMEL) | Type                                  | Value                 | Remark |
|--------------------------|---------------------------------------|-----------------------|--------|
| DNEL                     | Long-term systemic effects inhalation | 163 mg/m <sup>3</sup> |        |
|                          | Long-term local effects inhalation    | 918 mg/m <sup>3</sup> |        |

#### 8.1.5 Control banding

If applicable and available it will be listed below.

### 8.2. Exposure controls

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

#### 8.2.1 Appropriate engineering controls

Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks. Before use: check for peroxides and eliminate them. Measure the concentration in the air regularly. Measure the oxygen concentration in the air. Work under local exhaust/ventilation.

#### 8.2.2 Individual protection measures, such as personal protective equipment

Observe normal hygiene standards. Keep container tightly closed. Do not eat, drink or smoke during work.

##### a) Respiratory protection:

High vapour/gas concentration: self-contained respirator.

##### b) Hand protection:

Insulated gloves.

- materials (good resistance)

Leather, nitrile rubber, polyethylene.

- materials (poor resistance)

Butyl rubber, natural rubber.

##### c) Eye protection:

Protective goggles.

##### d) Skin protection:

Protective clothing.

#### 8.2.3 Environmental exposure controls:

See headings 6.2, 6.3 and 13

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

|               |               |
|---------------|---------------|
| Physical form | Liquefied gas |
| Odour         | Sweet odour   |
|               | Mild odour    |

Publication date: 2015-07-02

Reference number: 1260

Product number: 10340

Revision number: 0000

4 / 10

# isobutene, liquefied, under pressure

|                           |  |
|---------------------------|--|
| Odour threshold           | 46 mg/m <sup>3</sup>                                   |
| Colour                    | Colourless   |
| Particle size             | Not applicable (gas)                                   |
| Explosion limits          | 1.8 - 9.6 vol %<br>37 - 235 g/m <sup>3</sup>           |
| Flammability              | Extremely flammable gas.                               |
| Log Kow                   | 2.11 - 2.34 ; Experimental value                       |
| Dynamic viscosity         | No data available                                      |
| Kinematic viscosity       | No data available                                      |
| Melting point             | -140 °C  |
| Boiling point             | -7 °C  |
| Flash point               | -80 °C   |
| Evaporation rate          | No data available                                      |
| Relative vapour density   | 2  |
| Vapour pressure           | 2560 hPa ; 20 °C<br>6100 hPa ; 50 °C                   |
| Solubility                | water ; 263 mg/l ; 20 °C                               |
| Relative density          | 0.6 ; -7 °C  |
| Decomposition temperature | No data available                                      |
| Auto-ignition temperature | 465 °C   |
| Explosive properties      | No chemical group associated with explosive properties |
| Oxidising properties      | No chemical group associated with oxidising properties |
| pH                        | No data available                                      |

## 9.2. Other information

|                       |                               |
|-----------------------|-------------------------------|
| Specific conductivity | < 6000 pS/m                   |
| Critical temperature  | 144.7 °C                      |
| Critical pressure     | 40000 hPa                     |
| Surface tension       | 0.016 N/m                     |
| Absolute density      | 590 kg/m <sup>3</sup> ; -7 °C |

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

May build up electrostatic charges: risk of ignition. May be ignited by sparks. Gas/vapour spreads at floor level: ignition hazard.

### 10.2. Chemical stability

Unstable on exposure to air.

### 10.3. Possibility of hazardous reactions

Reacts slowly on exposure to air: peroxidation resulting in increased fire or explosion risk. Polymerizes on exposure to some compounds. Violent to explosive reaction with many compounds e.g.: with (strong) oxidizers, with (some) halogens and with (some) acids.

### 10.4. Conditions to avoid

Use spark-/explosionproof appliances and lighting system. Take precautions against electrostatic charges. Keep away from naked flames/heat. Keep away from ignition sources/sparks.

### 10.5. Incompatible materials

Combustible materials, oxidizing agents, (strong) acids, halogens.

### 10.6. Hazardous decomposition products

Upon combustion: CO and CO<sub>2</sub> are formed.

## SECTION 11: Toxicological information

### 11.1. Information on toxicological effects

#### 11.1.1 Test results

#### Acute toxicity

##### isobutene, liquefied, under pressure

| Route of exposure | Parameter | Method   | Value     | Exposure time | Species           | Value determination | Remark |
|-------------------|-----------|----------|-----------|---------------|-------------------|---------------------|--------|
| Oral              |           |          |           |               |                   | Data waiving        |        |
| Dermal            |           |          |           |               |                   | Data waiving        |        |
| Inhalation        | LC50      | OECD 403 | > 23 mg/l | 4 h           | Rat (male/female) | Experimental value  |        |

#### Conclusion

Not classified for acute toxicity

#### Corrosion/irritation

##### isobutene, liquefied, under pressure

Publication date: 2015-07-02

Reference number: 1260

Product number: 10340

Revision number: 0000

5 / 10

# isobutene, liquefied, under pressure

| Route of exposure | Result | Method | Exposure time | Time point | Species | Value determination | Remark |
|-------------------|--------|--------|---------------|------------|---------|---------------------|--------|
| Eye               |        |        |               |            |         | Data waiving        |        |
| Skin              |        |        |               |            |         | Data waiving        |        |

## Conclusion

Not classified as irritating to the skin  
 Not classified as irritating to the eyes  
 Not classified as irritating to the respiratory system

## Respiratory or skin sensitisation

### isobutene, liquefied, under pressure

| Route of exposure | Result | Method | Exposure time | Observation time point | Species | Value determination | Remark |
|-------------------|--------|--------|---------------|------------------------|---------|---------------------|--------|
| Skin              |        |        |               |                        |         | Data waiving        |        |
| Inhalation        |        |        |               |                        |         | Data waiving        |        |

## Conclusion

Not classified as sensitizing for skin  
 Not classified as sensitizing for inhalation

## Specific target organ toxicity

### isobutene, liquefied, under pressure

| Route of exposure   | Parameter | Method                 | Value                       | Organ | Effect    | Exposure time                   | Species             | Value determination |
|---------------------|-----------|------------------------|-----------------------------|-------|-----------|---------------------------------|---------------------|---------------------|
| Oral (stomach tube) | NOAEL     | Equivalent to OECD 407 | 146.6 mg/kg bw/day          |       | No effect | 28 day(s)                       | Rat (male/female)   | Experimental value  |
| Dermal              |           |                        |                             |       |           |                                 |                     | Data waiving        |
| Inhalation (gases)  | NOAEC     | Equivalent to OECD 453 | 18359 mg/m <sup>3</sup> air |       | No effect | 104 weeks (6h/day, 5 days/week) | Mouse (male/female) | Experimental value  |

## Conclusion

Not classified for subchronic toxicity

## Mutagenicity (in vitro)

### isobutene, liquefied, under pressure

| Result  | Method                 | Test substrate                | Effect    | Value determination |
|---|------------------------|-------------------------------|-----------|---------------------|
| Negative with metabolic activation, negative without metabolic activation | Equivalent to OECD 476 | Mouse (lymphoma L5178Y cells) | No effect | Experimental value  |
| Negative with metabolic activation, negative without metabolic activation | Ames test              | Bacteria (S.typhimurium)      | No effect | Experimental value  |

## Mutagenicity (in vivo)

### isobutene, liquefied, under pressure

| Result   | Method                 | Exposure time   | Test substrate | Organ | Value determination |
|----------|------------------------|-----------------|----------------|-------|---------------------|
| Negative | Equivalent to OECD 474 | 2 days (6h/day) | Mouse (male)   |       | Experimental value  |

## Carcinogenicity

### isobutene, liquefied, under pressure

| Route of exposure  | Parameter | Method                 | Value         | Exposure time                   | Species             | Value determination | Organ | Effect                 |
|--------------------|-----------|------------------------|---------------|---------------------------------|---------------------|---------------------|-------|------------------------|
| Inhalation (gases) | NOAEC     | Equivalent to OECD 453 | 18.4 mg/l air | 104 weeks (6h/day, 5 days/week) | Mouse (male/female) | Experimental value  |       | No carcinogenic effect |

## Reproductive toxicity

### isobutene, liquefied, under pressure

|                        | Parameter    | Method   | Value     | Exposure time              | Species           | Effect    | Organ | Value determination |
|------------------------|--------------|----------|-----------|----------------------------|-------------------|-----------|-------|---------------------|
| Developmental toxicity | NOAEC        | OECD 414 | 8000 ppm  | 17 days (gestation, daily) | Rat (male/female) | No effect |       | Experimental value  |
| Maternal toxicity      | NOAEC        | OECD 414 | 8000 ppm  | 17 days (gestation, daily) | Rat (female)      | No effect |       | Experimental value  |
| Effects on fertility   | NOAEC (P/F1) | OECD 422 | 18.4 mg/l |                            | Rat (male/female) | No effect |       | Experimental value  |

## Conclusion CMR

Publication date: 2015-07-02

Reference number: 1260

Product number: 10340

Revision number: 0000

6 / 10

# isobutene, liquefied, under pressure

Not classified for carcinogenicity  
Not classified for mutagenic or genotoxic toxicity  
Not classified for reprotoxic or developmental toxicity

## Toxicity other effects

isobutene, liquefied, under pressure

No (test) data available

## Chronic effects from short and long-term exposure

isobutene, liquefied, under pressure

No effects known.

## SECTION 12: Ecological information

### 12.1. Toxicity

isobutene, liquefied, under pressure

|   | Parameter | Method | Value             | Duration | Species             | Test design | Fresh/salt water | Value determination |
|---|-----------|--------|-------------------|----------|---------------------|-------------|------------------|---------------------|
| Acute toxicity fishes                   | LC50      |        | 30.72 mg/l        | 96 h     | Pimephales promelas |             |                  | QSAR                |
| Acute toxicity invertebrates            | LC50      |        | 14 mg/l - 30 mg/l | 48 h     | Daphnia magna       |             |                  | QSAR                |
| Toxicity algae and other aquatic plants | EC50      |        | 20.9 mg/l         | 72 h     | Algae               |             |                  | QSAR                |

#### Conclusion

Harmful to fishes  
Harmful to invertebrates (Daphnia)  
Harmful to algae  
Not classified as dangerous for the environment according to the criteria of Regulation (EC) No 1272/2008

### 12.2. Persistence and degradability

isobutene, liquefied, under pressure

#### Phototransformation air (DT50 air)

| Method | Value | Conc. OH-radicals    | Value determination |
|--------|-------|----------------------|---------------------|
|        | 7.5 h | 5E5 /cm <sup>3</sup> |                     |

#### Half-life soil (t1/2 soil)

| Method         | Value | Primary degradation/mineralisation | Value determination |
|----------------|-------|------------------------------------|---------------------|
| Not applicable |       |                                    |                     |

#### Conclusion

Readily biodegradable in water  
Readily biodegradable in water in anaerobic conditions

### 12.3. Bioaccumulative potential

isobutene, liquefied, under pressure

#### BCF fishes

| Parameter | Method | Value  | Duration | Species | Value determination |
|-----------|--------|--------|----------|---------|---------------------|
| BCF       |        | 7 - 19 |          | Pisces  |                     |

#### Log Kow

| Method | Remark | Value       | Temperature | Value determination |
|--------|--------|-------------|-------------|---------------------|
|        |        | 2.11 - 2.34 |             | Experimental value  |

#### Conclusion

Low potential for bioaccumulation (BCF < 500)

### 12.4. Mobility in soil

Not applicable (gas)

### 12.5. Results of PBT and vPvB assessment

Substance does not meet the criteria of PBT, nor the criteria of vPvB according to Annex XIII of Regulation (EC) No 1907/2006, so is neither PBT nor vPvB.

### 12.6. Other adverse effects

isobutene, liquefied, under pressure

Global warming potential (GWP)

Publication date: 2015-07-02

Reference number: 1260

Product number: 10340

Revision number: 0000

7 / 10

# isobutene, liquefied, under pressure

Not included in the list of fluorinated greenhouse gases (Regulation (EC) No 517/2014)

## Ozone-depleting potential (ODP)

Not classified as dangerous for the ozone layer (Regulation (EC) No 1005/2009)

## SECTION 13: Disposal considerations

The information in this section is a general description. If applicable and available, exposure scenarios are attached in annex. Always use the relevant exposure scenarios that correspond to your identified use.

### 13.1. Waste treatment methods

#### 13.1.1 Provisions relating to waste

Waste material code (Directive 2008/98/EC, Decision 2000/0532/EC).

16 05 04\* (gases in pressure containers and discarded chemicals: gases in pressure containers (including halons) containing dangerous substances).

Depending on branch of industry and production process, also other waste codes may be applicable. Hazardous waste according to Regulation (EU) No 1357/2014.

#### 13.1.2 Disposal methods

Refer to manufacturer/supplier for information on recovery/ recycling. Remove waste in accordance with local and/or national regulations. Hazardous waste shall not be mixed together with other waste. Different types of hazardous waste shall not be mixed together if this may entail a risk of pollution or create problems for the further management of the waste. Hazardous waste shall be managed responsibly. All entities that store, transport or handle hazardous waste shall take the necessary measures to prevent risks of pollution or damage to people or animals.

#### 13.1.3 Packaging/Container

Waste material code packaging (Directive 2008/98/EC).

15 01 10\* (packaging containing residues of or contaminated by dangerous substances).

## SECTION 14: Transport information

### Road (ADR)

#### 14.1. UN number

|           |      |
|-----------|------|
| UN number | 1055 |
|-----------|------|

#### 14.2. UN proper shipping name

|                      |             |
|----------------------|-------------|
| Proper shipping name | Isobutylene |
|----------------------|-------------|

#### 14.3. Transport hazard class(es)

|                              |    |
|------------------------------|----|
| Hazard identification number | 23 |
| Class                        | 2  |
| Classification code          | 2F |

#### 14.4. Packing group

|               |     |
|---------------|-----|
| Packing group |     |
| Labels        | 2.1 |

#### 14.5. Environmental hazards

|  |    |
|--|----|
| Environmentally hazardous substance mark | no |
|--|----|

#### 14.6. Special precautions for user

|                    |       |
|--------------------|-------|
| Special provisions | 662   |
| Limited quantities | none. |

### Rail (RID)

#### 14.1. UN number

|           |      |
|-----------|------|
| UN number | 1055 |
|-----------|------|

#### 14.2. UN proper shipping name

|                      |             |
|----------------------|-------------|
| Proper shipping name | Isobutylene |
|----------------------|-------------|

#### 14.3. Transport hazard class(es)

|                              |    |
|------------------------------|----|
| Hazard identification number | 23 |
| Class                        | 2  |
| Classification code          | 2F |

#### 14.4. Packing group

|               |           |
|---------------|-----------|
| Packing group |           |
| Labels        | 2.1 (+13) |

#### 14.5. Environmental hazards

|  |    |
|--|----|
| Environmentally hazardous substance mark | no |
|--|----|

#### 14.6. Special precautions for user

|                    |       |
|--------------------|-------|
| Special provisions | 662   |
| Limited quantities | none. |

### Inland waterways (ADN)

#### 14.1. UN number

|           |      |
|-----------|------|
| UN number | 1055 |
|-----------|------|

#### 14.2. UN proper shipping name

|                      |             |
|----------------------|-------------|
| Proper shipping name | Isobutylene |
|----------------------|-------------|

#### 14.3. Transport hazard class(es)

|                     |    |
|---------------------|----|
| Class               | 2  |
| Classification code | 2F |

Publication date: 2015-07-02

Reference number: 1260

Product number: 10340

Revision number: 0000

8 / 10



# isobutene, liquefied, under pressure

## 14.4. Packing group

|               |     |
|---------------|-----|
| Packing group |     |
| Labels        | 2.1 |

## 14.5. Environmental hazards

|  |    |
|--|----|
| Environmentally hazardous substance mark | no |
|--|----|

## 14.6. Special precautions for user

|                    |       |
|--------------------|-------|
| Special provisions | 662   |
| Limited quantities | none. |

## Sea (IMDG/IMSBC)

### 14.1. UN number

|           |      |
|-----------|------|
| UN number | 1055 |
|-----------|------|

### 14.2. UN proper shipping name

|                      |             |
|----------------------|-------------|
| Proper shipping name | Isobutylene |
|----------------------|-------------|

### 14.3. Transport hazard class(es)

|       |     |
|-------|-----|
| Class | 2.1 |
|-------|-----|

## 14.4. Packing group

|               |     |
|---------------|-----|
| Packing group |     |
| Labels        | 2.1 |

## 14.5. Environmental hazards

|  |    |
|--|----|
| Marine pollutant                         | -  |
| Environmentally hazardous substance mark | no |

## 14.6. Special precautions for user

|                    |       |
|--------------------|-------|
| Special provisions |       |
| Limited quantities | none. |

## 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code

|                          |                |
|--------------------------|----------------|
| Annex II of MARPOL 73/78 | Not applicable |
|--------------------------|----------------|

## Air (ICAO-TI/IATA-DGR)

### 14.1. UN number

|           |      |
|-----------|------|
| UN number | 1055 |
|-----------|------|

### 14.2. UN proper shipping name

|                      |             |
|----------------------|-------------|
| Proper shipping name | Isobutylene |
|----------------------|-------------|

### 14.3. Transport hazard class(es)

|       |     |
|-------|-----|
| Class | 2.1 |
|-------|-----|

## 14.4. Packing group

|               |     |
|---------------|-----|
| Packing group |     |
| Labels        | 2.1 |

## 14.5. Environmental hazards

|  |    |
|--|----|
| Environmentally hazardous substance mark | no |
|--|----|

## 14.6. Special precautions for user

|   |    |
|---|----|
| Special provisions  | A1 |
| Passenger and cargo transport: limited quantities: maximum net quantity per packaging |    |

## SECTION 15: Regulatory information

### 15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

#### European legislation:

VOC content Directive 2010/75/EU

| VOC content | Remark |
|-------------|--------|
| 100 %       |        |

REACH Annex XVII - Restriction

Subject to restrictions of Annex XVII of Regulation (EC) No. 1907/2006: restrictions on the manufacture, placing on the market and use of certain dangerous substances, mixtures and articles.

|                 | Designation of the substance, of the group of substances or of the mixture  | Conditions of restriction  |
|-----------------|---|--|
| 2-methylpropene | Substances classified as flammable gases category 1 or 2, flammable liquids categories 1, 2 or 3, flammable solids category 1 or 2, substances and mixtures which, in contact with water, emit flammable gases, category 1, 2 or 3, pyrophoric liquids category 1 or pyrophoric solids category 1, regardless of whether they appear in Part 3 of Annex VI to that Regulation or not. | 1. Shall not be used, as substance or as mixtures in aerosol dispensers where these aerosol dispensers are intended for supply to the general public for entertainment and decorative purposes such as the following:<br>— metallic glitter intended mainly for decoration,<br>— artificial snow and frost,<br>— “whoopee” cushions,<br>— silly string aerosols,<br>— imitation excrement,<br>— horns for parties,<br>— decorative flakes and foams,<br>— artificial cobwebs,<br>— stink bombs.2. Without prejudice to the application of other Community provisions on the classification, packaging and labelling of substances, suppliers shall ensure before the |

Publication date: 2015-07-02

Reference number: 1260

Product number: 10340

Revision number: 0000

9 / 10

# isobutene, liquefied, under pressure

placing on the market that the packaging of aerosol dispensers referred to above is marked visibly, legibly and indelibly with:  
"For professional users only". 3. By way of derogation, paragraphs 1 and 2 shall not apply to the aerosol dispensers referred to Article 8 (1a) of Council Directive 75/ 324/EEC.4. The aerosol dispensers referred to in paragraphs 1 and 2 shall not be placed on the market unless they conform to the requirements indicated.

## National legislation The Netherlands

|  |   |
|--|---|
| Waste identification (the Netherlands) | LWCA (the Netherlands): KGA category 06 |
| Waterbezwaarlijkheid                   | 9                                       |

## National legislation Germany

|         |   |
|---------|---|
| WGK     | nwg; Classification non-water polluting in compliance with Verwaltungsvorschrift wassergefährdender Stoffe (VwVwS) of 27 July 2005 (Anhang 1) |
| TA-Luft | 5.2.5   |

## National legislation France

No data available

## National legislation Belgium

No data available

## Other relevant data

|                  |                |
|------------------|----------------|
| TLV - Carcinogen | iso-Butene; A4 |
|------------------|----------------|

## 15.2. Chemical safety assessment

A chemical safety assessment has been performed.

## SECTION 16: Other information

### Full text of any H-statements referred to under headings 2 and 3:

H220 Extremely flammable gas.

H280 Contains gas under pressure; may explode if heated.

(\*) = INTERNAL CLASSIFICATION BY BIG

PBT-substances = persistent, bioaccumulative and toxic substances

CLP (EU-GHS) Classification, labelling and packaging (Globally Harmonised System in Europe)

The information in this safety data sheet is based on data and samples provided to BIG. The sheet was written to the best of our ability and according to the state of knowledge at that time. The safety data sheet only constitutes a guideline for the safe handling, use, consumption, storage, transport and disposal of the substances/preparations/mixtures mentioned under point 1. New safety data sheets are written from time to time. Only the most recent versions may be used. Old versions must be destroyed. Unless indicated otherwise word for word on the safety data sheet, the information does not apply to substances/preparations/mixtures in purer form, mixed with other substances or in processes. The safety data sheet offers no quality specification for the substances/preparations/mixtures in question. Compliance with the instructions in this safety data sheet does not release the user from the obligation to take all measures dictated by common sense, regulations and recommendations or which are necessary and/or useful based on the real applicable circumstances. BIG does not guarantee the accuracy or exhaustiveness of the information provided and cannot be held liable for any changes by third parties. This safety data sheet is only to be used within the European Union, Switzerland, Iceland, Norway and Liechtenstein. Any use outside of this area is at your own risk. Use of this safety data sheet is subject to the licence and liability limiting conditions as stated in your BIG licence agreement or when this is failing the general conditions of BIG. All intellectual property rights to this sheet are the property of BIG and its distribution and reproduction are limited. Consult the mentioned agreement/conditions for details.

Publication date: 2015-07-02

Reference number: 1260

Product number: 10340

Revision number: 0000

10 / 10